


MINIBAR 40L

Reference	AMS-MBAB005
Door Material	Solid
External Dimensions(mm) Width x Height x Depth	400x552x442
Internal Dimensions (mm) Width x Height x Depth	330x475x240
Volume (l)	40
Temperature Range	0-8 °C
Rating Power(w)	65
Power Consumption	0.85KW.h/24H
Color	Black
Rating Voltage/Frequency	AC 220/110V, 50Hz/60Hz
Loading Qty. 20'/40'/40HQ'	165/360/480

OTHERS

- »»No compressor, no mechanical movements, silent running
- »»Environmental friendly, no Freon
- »»CE Approved
- »»Electronic thermostat, intelligent automatic defrosting system controlled by an IC chip.
- »»SecondGeneration of absorption cooling technique, totally noiseless when working.
- »»Foaming with clopentane (C5H10) , a CFC Free thermal insulation with ultra cooling efficiency;
- »»Over-head light design, low rated power LED light (magnet sensor)
- »»100% antibacterial removable soft PVC door seal.
- »»HIPS antibacterial liner to dispel the odor and keep the original taste.
- »»Thermal regulator for convenient adjustment
- »»2 shelves (and 2 bottle racks)
- »»easy-opened doorknob
- »»Lock and Master Key Option Available
- »»Reversible Door Opening Available
- »»Door open indicator Available

Details of MINIBAR 40L



Packing Information

Psc per carton	1
Carton size (mm)	500x460x585
Net/gross weight (kg)	17.0 / 18.8